

# Adjustment slide

## Type VS



### Dovetail adjustment slide

#### Technical data

stroke (standard sizes)	10 to 75 mm
special solutions	up to 300 mm
max. load	3 to 441 N
special solutions in grey cast iron	up to 1395 N
operating temperature	0 bis +80°C
special solutions	-45 to +120°C
coefficient of friction	0,1
with special coating	0,05
length (standard sizes)	15 to 160 mm
width (standard sizes)	10 to 100 mm
material	aluminium
alternative	grey cast iron



#### Surface options

- anodized
- chemically nickel-plated
- special coating for very low light reflection

#### Drive options

- manual, with micrometerscrew
- manual, with handwheel
- motorized

#### More options

- individual drilling pattern
- multi-axis design
- clamping type ZL or type F
- position indicator
- reinforced spindle bearing
- conical feed rail

#### Main advantages

- simple and compact design
- maintenance free
- flexible customization options
- long service life
- can be combined with the ERO modular system



We make it moving

---

ERO-Führungen GmbH  
Weißkreuzstraße 16  
79843 Löffingen-Unadingen  
Deutschland

+49 (0) 7707 158-0  
[info@ero-fuehrungen.de](mailto:info@ero-fuehrungen.de)  
[www.ero-fuehrungen.de](http://www.ero-fuehrungen.de)